New Product Release




Tool-Less 19-Inch Blanking Panels.

New to Cooper B-Line's standard product offering comes a range of Quick Fit 19-inch blanking panels.

Incorporating tool-less ¼-turn fixings these panels can be easily and quickly fitted to all EIA-310-D compliant 19-inch enclosures having19-inch square pierced mounting rails.

Ideal for blanking off unused portions of the front 19-inch mounting area these panels are available in 1U, 2U and 5U increments to suit all applications.




Technical Specification					
Sizes	1U	2U	5U		
Material	Panel - Mild steel 1.2mm thick (18swg) Fixings – Black Polycarbonate				
Finish	Painted RAL9005 Black				
Fixing Type	Too	ol-less ¼ Turn Fastene	rs		

Simple Operation

Assembly

- 1. Locate the fixing into the panel
- 2. Tap the actuating pin into the receptacle as shown in "B". When the slot in the head of the actuating pin is horizontal the fixing is latched.





Panel Mounting.

- A. Rotate actuating pins so that the slot in the head is vertical. Locate the appropriate panel in the relevant empty unit position.
- B. Turn each of the ¼ turn fixings through 90 degrees so slots in actuating pins are horizontal securely latching the panel in position.


Panel Reposition.

 Turn each of the ¼ turn fixings through 90 degrees to unlatch the panel and reposition as necessary.



New Product Release

Blanking Panel Application.





This design offers the ideal solution

where users need to blank off unused 19-inch aperture locations. Particularly useful in active cabinet installations these panels can be quickly and easily fitted in position to optimise air management within the cabinet consequently maximising cooling efficiencies.



Order Code	Description	Shipping Weight
PPS1UQFB	1U 19-Inch Quick Fit Blanking Panel. 482.6mm Wide x 44.0mm High Finished RAL9005 Black	0.25kg
PPS2UQFB	2U 19-Inch Quick Fit Blanking Panel. 482.6mm Wide x 89.0mm High Finished RAL9005 Black	0.45kg
PPS5UQFB	2U 19-Inch Quick Fit Blanking Panel. 482.6mm Wide x 222.0mm High Finished RAL9005 Black	1.1kg

